

Single-phase dry-type transformers 0.5 kV for electric furnaces of various application

Type	Rated power, кVA	Rated voltage of windings, V		Number of tapping positions	Mass, kg	Length x width x height, mm
		HV	LV			
OC-25/0,5-УХЛ4А	12,5-8,34	220 или 380	12,82-6,41; 8,54-4,27	4	136	540 x 421 x 555
OC-25/0,5-УХЛ4М	20-13,3	220 или 380	8,54-4,27	>>	155	540 x 421 x 555
OC-63/0,5-УХЛ4	50-15	380	84,4-25,3	10	330	728 x 435 x 587
	50-15	220 и 380	84,4-12,65	20	330	
OCY-40/0,5-УХЛ4	40	220 или 380	20,92-6,3	10	280	720 x 529 x 676
OC3-100/0,5-УХЛ4	80-50	380	76-47,5; 38-23,75	10	905	1035 x 805 x 1345
OC3K-100/0,5-УХЛ4	114-71,3	380	38-23,75	10	820	870 x 695 x 1164
OC-125/0,5-УХЛ4А	100-37,5	220 или 380	49,0-4,6	12	466	800 x 615 x 885
OC-125/0,5-УХЛ4М	125-37,5		49,0-4,6	12	499	
OC-125/0,5-УХЛ4А	90-33,7		91,8-34,3; 183,6-68,6	8	466	
OC3-250/0,5-УХЛ4	250-96,5	380	71,3-27,5	6	2780	2052 x 900 x 2110
OC3K-250/0,5-УХЛ4	250-90,5	220 или 380	83,3-32,2	6	2780	2052 x 900 x 2110
OCKP-250/0,5-УХЛ4	250	380	84,4	2	1400	1080 x 775 x 1280
	150		50,7			
OCKP-320/0,5-УХЛ4	250	380	42,2-36,8-32,6	3	1400	1080 x 775 x 1280