

Three-phase dry-type transformers 0.5 kV for electric furnaces of various application

Type	Rated power, кVA	Rated voltage of windings, V		Connection of windings	Number of tapping positions	Mass, kg	Length x width x height, mm
		HV	LV				
ТС-63/0,5-УХЛ4-А	40-26,2	380 или 220	23,75-4,58	Д/Д-0; У/Д-1; У/У-0	12	311	930 x 517 x 656
ТС-63/0,5-УХЛ4-М	50-33,4	380 или 220	23,75-4,58	Д/Д-0; У/Д-1; У/У-0	>>	380	930 x 517 x 656
ТСУ-50/0,5-УХЛ4	40-26,2	380 или 220	23,75-4,58	Д/Д-0	12	311	930 x 517 x 656
ТСС-160/0,5-У3-А	140-60,8	380	42,4-5,32	Д-У/У-Д	16	843	1120 x 627 x 922
	140	380±5%	54,3	У/У-0	3	846	1120 x 627 x 922
ТСС-160/0,5-У3-В	160-69,3	380	42,4-5,32	Д-У/У-Д	16	985	1120 x 627 x 922
	160	380±5%	54,3	У/У-0	3	996	1120 x 627 x 922
ТСС-400/0,5-УХЛ4	345	380	63,6-15,9	У/У-0	>>	1600	1510 x 620 x 1056
			36,6-9,165	У/Д-11			
	345	220	63,6-15,9	Д/У-11	>>	>>	>>
			36,6-9,165	Д/Д-0			
	325	380	34,6-8,65	Д/Д-0	>>	>>	>>
			60-15	Д/У-11			
	187	220	20-5	Д/Д-0	>>	>>	>>
		34,6-8,65	Д/У-11				
	315	380	64	У/У-0	1	>>	>>