

Three-phase and single-phase transformers 6 kV and 10 kV

Type	Rated power, kVA	Rated voltage of windings, V		Connection of windings	Number of tapping positions	Cooling system	Mass, t	Length x width x height, mm
		HV	LV					
ЭОМК-390/10	250	6000; 10000	117,5-95	1/1-0	3	ONAN	2,6	1740 x 1135 x 2700
ЭОМК-600/10	400	6000; 10000	131-102	>>	>>	ONAN	3,22	1800 x 1280 x 2920
ЭТДЦП-1600/10-УХЛ4	800-303	6000; 10000	211,8-80,0	Д-У/Д-0-11	12	ОFAF	8,0	2500 x 1700 x 2380
ЭТДЦП-2500/10-УХЛ4	1600-655	6000; 10000	220-90,2	>>	>>	ОFAF	11,5	3535 x 1800 x 2380
ЭТДЦП-4000/10-УХЛ4	2500-2500-1305	6000; 10000	230-95,4	>>	>>	ОFAF	14,3	3557 x 1950 x 2570
ЭТЦПК-12500/10-У3	8000-3020	6000; 10000	318-120	Д/Д-0; У/Д-11	>>	ОFWF	25,0	4130 x 2240 x 4383
ЭТЦП-10000/10-УХЛ4	5000-5000-2887	6000; 10000	260-104	Д-У/Д-0-11	>>	ОFWF	24,0	3631 x 2280 x 3120