

Three-phase and single-phase transformers 6 kV and 10 kV for induction electric furnaces

| Type | Rated power, кVA | Rated voltage of windings, V | | Voltage regulation | Number of tapping positions | Mass, t | Length x width x height, mm |
|----------------------|------------------|------------------------------|--------------------|--------------------|-----------------------------|---------|-----------------------------|
| | | HV | LV | | | | |
| ЭОМПИ-1000/10-УХЛ4 | 400-76 | 6000; 6300; 10000 | 510-85 | ПБВ | 11 | 3,5 | 1720 x 1525 x 2146 |
| ЭОМПИ-1600/10-УХЛ4 | 630-110 | 6000 | 511-81 | >> | >> | 4,8 | 1895 x 1530 x 2270 |
| | 630-110 | 10000 | 510-79 | >> | >> | >> | >> |
| | 630-168 | 6000 | 561-118 | >> | >> | >> | >> |
| ЭОМПИ-2000/10-УХЛ4 | 1000-200 | 6000; 10000 | 510-91; 1020-182 | >> | >> | 5,8 | 2200 x 1490 x 2445 |
| | 1000-200 | 6000; 10000 | 990-177; 1980-354 | >> | >> | >> | >> |
| ЭОМНИ-2700/10-У3 | 1600-400 | 6000 | 527-105; 1054-210 | РПН | 17 | 10,3 | 2700 x 1965 x 3610 |
| | 2500-625 | 10000 | 527-105; 1054-210 | >> | >> | >> | >> |
| ЭОМНИ-4200/10-УХЛ4 | 2500-625 | 6000; 10000 | 1459-292; 2919-584 | >> | >> | 12,9 | 2700 x 2450 x 3970 |
| ЭОМНИ-4200/10-У3 | 2500-625 | 6000; 10000 | 1050-210; 2100-422 | >> | >> | 12,9 | 2700 x 2450 x 3970 |
| ЭТМП-1250/10-У3 | 1000-200 | 6000; 10000 | 1020-182; 510-91 | ПБВ | 11 | 7,0 | 2280 x 1850 x 3200 |
| ЭТМНИ-2000/10-УХЛ4 | 1600-1600-400 | 6000; 10000 | 1057-211 | РПН | 17 | 13,8 | 3500 x 1910 x 3560 |
| ЭТМНИ-2500/10-УХЛ4 | 1000-1000-400 | 6000 | 520-181 | >> | 9 | 9,9 | 2550 x 2050 x 2800 |
| ЭТЦНКИ-5000/10-УХЛ4 | 2500-624 | 6000; 10000 | 2100-420 | >> | 17 | 15,2 | 3502 x 1886 x 3600 |
| | | 6000; 10000 | 1050-210 | >> | >> | >> | >> |
| ЭТЦНКИ-8000/10-УХЛ4 | 4000-790 | 6000; 10000 | 2403-402 | >> | 23 | 32 | 4200 x 3170 x 3560 |
| ЭТЦНКИ-10000/10-УХЛ4 | 5600-1070 | 6000 | 2397-388 | >> | >> | 36,7 | 4450 x 3250 x 3750 |
| | 5600-1070 | 10000 | 2400-388 | >> | >> | >> | >> |
| ЭТЦНКИ-12500/10-УХЛ4 | 7100-1341 | 6000 | 2403-384 | >> | >> | 40,0 | 4350 x 2890 x 4155 |
| | 7100-1350 | 10000 | 2391-385 | >> | >> | >> | >> |