

Single-phase transformers 6 kV and 10 kV for electroslag remelting furnaces

Type	Rated power, кVA	Rated voltage of windings, V		Voltage regulation.	Number of tapping positions.	Cooling system	Mass, t	Length x width x height, mm
		HV	LV					
ЭОМНШМ-1600/10-УХЛ4	630-630-278	6000	80-28,5	РПН	90	ONAN	10,325	3030 x 1760 x 3530
	630-630-283	10000	80-28,9	>>	>>	>>	10,325	
ЭОДЦНШМ-2500/10-УХЛ4	1000-1000-545	6000	105-37,8	>>	>>	OFAF	13,0	3270 x 1550 x 3730
	1000-1000-551	10000	105-38,4	>>	>>	>>	13,0	
ЭОДЦНШ-2500/10-УХЛ4	1000-519	6000	394-194	>>	49	>>	13,0	3270 x 1550 x 3730
	1000-524	10000	394-194	>>	>>	>>	13,0	
ЭОДЦНШМ-4000/10-УХЛ4	1600-1600-680	6000	116-32,4	>>	90	>>	13,7	2930 x 2208 x 3635
	1600-1600-733	10000	116-34,9	>>	>>	>>	13,7	
ЭОДЦНШМ-4800/10-УХЛ4	2500-2500-1217	6000	122,4-43,5	>>	>>	>>	19,7	3360 x 2400 x 3850
	2500-2500-1418	10000	122,4-51,7	>>	>>	>>	19,7	
ЭОЦНШ-6300/10-У3	3200-1555	6000	122,4-43,5	>>	>>	OFWF	19,7	3700 x 2400 x 3850
	3200-1815	10000	122,0-51,7	>>	>>	>>	19,7	
ЭОЦНШ-8000/10-УХЛ4	3820-2010	10000	152,7-56,6	>>	>>	>>	22,5	3700 x 2400 x 3850
ЭОЦНШ-12500/10-У3	5000-2450	6000	160-41,2	>>	>>	>>	34,0	4250 x 3000 x 4000
	5000-2470	10000	160-41,6	>>	>>	>>	34,0	
ЭОЦНШ-16000/10-УХЛ4	7200-7200-2470	10000	160-41,6	>>	>>	>>	34,2	4250 x 3000 x 4000