

**Three-phase transformers 6 kV, 10 kV and 0.5 kV for direct current electric furnaces**

Type	Rated power, кVA	Rated voltage, V			Connection of windings	Voltage regulation	Number of tapping positions	Cooling system	Mass, t	Length x width x height, mm
		supply winding	rectifier windings	converter unit						
ТЦПУ-4000/10-ЭПУХЛ4	1176-482 >>	6000 10000	240-98,4 >>	280,8 >>	У/УнрУнр-0-6 Д/УнрУнр-11-5	ПБВ >>	12 >>	OFWF OFWF	12,2 >>	3230 x 1830 x 2380 >>
ТРДЦП-4000/10-УХЛ4	1674-904	6000; 10000	236,8-80	319,7	Д/ДД-0-0	>>	>>	OFAF	14,21	3270 x 1940 x 2700
ТРДЦП-5000/10-УХЛ4	2575-1305	6000; 10000	260-92	351,0	>>	>>	>>	OFAF	14,33	3270 x 1940 x 2700
ТРЦП-12500/10-УХЛ4	5110-2339	6000; 10000	347-136	468	>>	>>	>>	OFWF	23,85	2850 x 2280 x 3130
ТРСП-500/6	506	6000	91,1	123	У/ДУ-1-0	>>	1	AN	2,6	1680 x 850 x 1354
ТРСП-630/0,5-УХЛ4	570	380	133,5	180	Д/ДД-0	>>	2	AN	2,72	1700 x 1050 x 1700