

**Three-phase oil-immersed transformer 6 kV, 10 kV and 35 kV for electric furnaces of various application**

Type	Rated power, кVA	Rated voltage of windings, V		Connection of windings	Voltage regulation	Number of tapping positions	Cooling system	Mass, t	Length x width x height, mm
		HV	LV						
ЭТЦХ-5000/10-У3 (Т3)	2500-2000	6000	176,5-88	Д/Д-0	ПБВ	5	OFWF	17,9	3380 x 3165 x 3760
	2500-2000	10500	176,5-88	У/Д-11	>>	>>	>>	17,9	3380 x 3165 x 3760
	3500-3150	10000	309-216	Д/У-11	>>	>>	>>	17,9	3380 x 3165 x 3760
	3500-3150	10500	371-260	>>	>>	>>	>>	17,9	3380 x 3165 x 3760
	3500-2450	6000	159,5-112	Д/Д-0	>>	>>	>>	17,9	3380 x 3165 x 3760
	3500-2450	10500	159,5-112	У/Д-11	>>	>>	>>	17,9	3380 x 3165 x 3760
ЭТЦХ-5000/10-98У3	3500-3150	10000	143-100	Д/Д-0	>>	>>	>>	17,9	3380 x 2650 x 3760
ЭТЦХ-10000/10-У3 (Т3)	4500-3600	6000	178-89	>>	>>	>>	>>	23,6	3910 x 2655 x 4360
	4500-3600	10000	178-89	У/Д-11	>>	>>	>>	23,6	3910 x 2655 x 4360
ЭТЦХ-10000/35-У3 (Т3)	10500-7020	10000	158-105,5	Д/Д-0	>>	8	>>	43	5190 x 2976 x 5340
	10500-7020	35000	158-105,5	>>	>>	>>	>>	43	5190 x 2976 x 5340
	10500-7020	35000	316-211	>>	>>	>>	>>	40,8	4994 x 2976 x 4698
ЭТЦН-12500/10-92-У3	5000-2070	6000	200-69,3	Д-У/Д-0-11	РПН	10	>>	30,3	3710 x 2770 x 3830
ЭТЦПР-10000/10-УХЛ4	4500-3000	6000	148,1-74,1	Д/Д-0	ПБВ	5	>>	22,0	3900 x 2560 x 4375